

---

# Standard Rotating Arm Flagpole

big effect, small price

---



# Standard Rotating Arm Flagpole

## big effect, small price



Standard Rotating Arm Flagpole



Standard Rotating Arm Flagpole with aluminium head

Theft-proof flagpole, ideal for displaying advertising flags. This cost-effective flagpole was conceived for permanent use and is provided with a rotating arm to show the whole flag optimally even when there is no wind. Best suited to industry, shopping centres, restaurants, etc. This flagpole can be installed without problems even in exposed locations.

This well-established, easy-care Flagpole is produced in sizes from 5 m to 12 m in one or two-piece versions. Thanks to the rotating arm (not hoistable), the full size of the flag

can be seen even when there is no wind. The flag is fixed lengthways by the supplied plastic tubes and does not create any noise. The attachable rotating arm, not manipulable from the ground, offers the best possible protection from theft and vandalism. The arm turns freely in the wind a full 360°. To simplify the changing of the flag we recommend a hinged base plate. Smaller flagpoles can also easily be installed with a ground tube or a ground socket with center ring. The flagpole equipped with plastic head comes as standard, an aluminium head is optional.

### Technical Data: Standard Rotating Arm Flagpole

Height	Version	Diameter	Weight	Pack Length
5 m	1-piece	60 or 80 mm	6,5 or 11 kg	5 - 5,5 m
	2-piece	60/60 mm or 80/60 mm	7,0 or 9,5 kg	3 - 3,5 m
6 m	1-piece	60 or 80 mm	7,5 or 13 kg	6 - 6,5 m
	2-piece	60/60 mm or 80/60 mm	8 or 11 kg	3 - 3,5 m
7 m	1-piece	80 mm	14,6 kg	7 - 7,5 m
	2-piece	80/60 mm	12,5 kg	4 - 4,5 m
8 m	2-piece	80/60 mm or 100/80 mm	13,8 or 20,5 kg	4 - 4,5 m
9 m	2-piece	101/80 mm	23,0 kg	6 m
10 m	2-piece	101/80 mm	25,2 kg	6 m
11 m	2-piece	101/80 mm	26,9 kg	6 m
12 m	2-piece	101/80 mm	29,6 kg	6,5 m

Flagpoles are aluminum, available in colorless anodized (silver grey) or powder-coated white (RAL 9010) versions. More colors on request.

#### Maintenance:

The flagpole does not require maintenance. Check plastic tubes when changing the flag and replace when necessary.

#### Remarks:

The distance between two Flagpoles must total the minimum twice the flag width plus 40 cm! For the placing of a hinged base plate, please refer to the separate operating and assembly instructions. In stormy weather (Beaufort 8+ winds) the flag must be taken down for safety reasons.