
Crank Rotating Arm Flagpole sure to catch the eye



Crank Rotating Arm Flagpole

sure to catch the eye



Crank Rotating Arm Flagpole



Crank Rotating Arm Flagpole with aluminum head

This flagpole is ideal for advertising and always displays the flag at its full size. Thanks to the internal halyard, it is vandal and theft proof. The flag can be hoisted and changed without the strenuous task of removing the flagpole.

The 5 m to 12 m high flagpole is inbuilt with a winch that is operated with a removable hand crank. The rotating arm of the flagpole turns freely 360° in the wind and always faces the optimal wind direction. The special rope, with its breaking

load of 600 kg, is designed to bear a heavy load. Additionally a spring mounted rotator is attached to the halyard and protects the rope from extreme over-tension. The flag is slid into the flag-support beam with the supplied plastic cord and is secured with finishing plastic plugs. The counterweight and the lateral fixing of the flag with the supplied plastic tubes allow smooth lowering of the flag. The two-piece flagpole is fixed with a ground socket and the appropriate center ring.

Technical Data: Crank Rotating Arm Flagpole

Height	Version	Diameter	Weight	Pack Length
5 m	2-piece	100/80 mm	16,0 kg	3,0 m
6 m	2-piece	100/80 mm	17,2 kg	3,5 m
7 m	2-piece	100/80 mm	18,9 kg	4,0 m
8 m	2-piece	100/80 mm	21,5 kg	4,5 m
9 m	2-piece	101/80 mm	24,0 kg	6,0 m
10 m	2-piece	101/80 mm	26,2 kg	6,0 m
11 m	2-piece	101/80 mm	27,9 kg	6,0 m
12 m	2-piece	101/80 mm	30,0 kg	6,5 m

Flagpoles are aluminum, available in colorless anodized (silver grey) or powder-coated white (RAL 9010) versions. More colors on request.

Maintenance:

The plastic tubes must be checked after strong winds and from time to time. Missing tubes or torn loops on the flag must be replaced immediately. The flag-support beam must always be pulled all the way up into the u-profiled Arm – if the tension should relax the rope must be re-tightened with the hand crank. It is very important to replace worn parts immediately.

Remarks:

In stormy weather (Beaufort 8+ winds) the flag must be taken down for safety reasons. When hoisting or lowering the flag, the halyard must always be kept taut. Therefore, always attach the weight, with or without the flag. It is imperative that the flag has a loop for the supplied plastic tubes every 60 cm as this will hinder a too great sail effect and the overturning of the flag over the arm. In very exposed locations we recommend the Standard Rotating Arm Flagpole. The distance between two Flagpoles must total at least twice the flag width plus 40 cm.