

---

# Deluxe small access door mast

## Safe, comfortable and sturdy

---



# Deluxe small access door mast

## Safe, comfortable and sturdy



Deluxe small access door



Deluxe Lockup Flagpole

This further refined advertising mast combines the advantages of the proven access door mast with those of the access door cantilever arm deluxe mast. Thanks to its interior hoisting mechanism, this mast is particularly suitable for pedestrian locations such as pedestrian precincts, public buildings or shopping streets.

The access door deluxe mast is available in sizes of 5m to 12m and is supplied with ground sleeve and suitable centring ring as well as provided with a small cast aluminium lockable access door. After opening the lock which renders the mast safe from theft and vandalism, the flag can be ma-

nually hoisted with the interior hauling cable. The hoisting and change of the flag is without the strenuous laying of the mast, a generous opening makes for problem-free stowing of the rope. The hauling cable is drawn outwards from the inner tube via a pulley on the aluminium turning head and an inserted swivel prevents the over-winding of the hauling cable. This is designed for a very strong load and has a tearing resistance of 600 kg. The flag is attached to the end of the hoisting line with a galvanized ring and laterally fastened to the mast with the plastic sleeves provided. A counter-weight ensures the flag is reeled in smoothly.

### Technical Data: Mast access door

Height	Version	Diameter	Weight	Pack Length
5 m	1-piece	80 mm	10 kg	5,5 m
6 m	1-piece	80 mm	12 kg	6,5 m
7 m	1-piece	80 mm	13,6 kg	7,5 m
8 m	2-piece	100/80 mm	19,5 kg	4,5 m
9 m	2-piece	101/80 mm	22,0 kg	6 m
10 m	2-piece	101/80 mm	24,2 kg	6 m
11 m	2-piece	101/80 mm	25,9 kg	6 m
12 m	2-piece	101/80 mm	28,0 kg	6,5 m

The masts are available in colourless anodised aluminium (silver-grey) or powder coat painted white (RAL 9010). Further colours are available on request.

#### Maintenance:

The plastic sockets must be regularly tested, faulty access sockets or torn straps on the flag must be replaced immediately. The timely exchange of worn parts is very important.

#### Remarks:

Always affix the counter weight whether with or without the flag. The flag must have a strap for a plastic socket every 60cms. Always attach the weight to a flag strap and on the lowest plastic socket! During storms (windspeed force 8 Beaufort scale) the flag must be taken down for safety reasons.